

ROTAX° ENGINE	1200 4-TEC
Engine details	Liquid-cooled, four-stroke D.O.H.C. dry sump
Cylinders	3
Displacement	1170.7 cc

91 mm Stroke 60 mm Maximum engine speed 7800 RPM EFI Carburation

Recommended fuel type Unleaded Minimum octane 95 Fuel tank 40 liters

POWERTRAIN

POTAX® FNICINIF

Drive clutch type	eDrive II
Driven clutch type	QRS SS
Small sprocket number of teeth	1st gear = 3.86:1
Large sprocket number of teeth	2nd gear = 2.3:1
Drive sprocket	8
Brake system	Hydraulic brake with braided steel brake line, plastic master cylinder

COLOUR



DIMENSIONS

Vehicle overall length	3280 mm
Vehicle overall width	1290 mm
Vehicle overall height	1400 mm
Ski stance	1102 (-42) mm
Track nominal width	600 mm
Track nominal length	3968 mm
Track profile height	32 mm Ice Ripper (studded)

SUSPENSION

Front suspension	A-LFS
Front shock	HPG 36
Rear suspension	PPS-6900-F
Center shock	HPG 36
Rear shock	2 x HPG 36

FEATURES

Frame	L-XU
Skis	Blade XC
Seating	Modular, 1+1
Handlebar	U-type steel with hooks, mountain strap
Riser block height	130 mm
Starter	Electric
Reverse	Mechanical (2F-N-R)

Heated throttle lever	Standard
Heated grips	Standard
Gauge	Multifunction
Mirrors	Standard
Windshield	High (510 mm), one piece
Hitch	Standard
Visor Plug front / rear	-
12V power outlet	Front



