## **©OUTLANDER™ 6x6 PRO 1000 T3**

## **HIGHLIGHTS**

- Rotax® V-twin engine
- Continuously Variable Transmission (CVT) with Extra Low L-gear
- 318 kg capacity Dual-Level™ cargo box with modular accessories
- 1,361 kg WARN<sup>†</sup> winch with roller fairlead
- Tri-Mode Dynamic Power Steering (DPS™)
- 26-in. 6-ply Carlisle<sup>†</sup> ACT HD radial tires
- Double Torsional Trailing arm Independent (TTI2) rear suspension
- 750 kg towing capacity
- 12-in. cast-aluminum wheels

- · Relocated air intakes
- Quick release sway bar
- High-strength, multifunction racks with LinQ<sup>™</sup> quick-attach accessory system
- Double A-arm front suspension with increased suspension preload and dive-control geometry



Green

ENGINE	1000	
Туре	Rotax 976 cc V-twin, liquid cooled	
Fuel Delivery System	Electronic Fuel Injection (EFI)	
Transmission	CVT, P / R / N / H / Extra Low L, standard engine braking	
Drive Train	Selectable 4WD / 6WD with Visco-Lok <sup>‡</sup> QE auto-locking front differential	
Power Steering	Tri-Mode Dynamic Power Steering (DPS)	

SUSPENSIONS	
Front Suspension	Double A-arm with increased suspension preload 22.9 cm travel
Front Shocks	0il
Rear Suspension	Double Torsional Trailing arm Independent (TTI2) with quick-release sway bar 23.6 cm travel
Rear Shocks	0il

BRAKES	
Front	Dual 214 mm ventilated disc brakes with hydraulic twin-piston calipers
Rear	Dual 214 mm ventilated disc brakes with hydraulic twin-piston calipers

TIRES / WHEEL	S
Front Tires	Carlisle <sup>†</sup> ACT HD 26 x 8 x 12-in. (66 x 20.3 x 30.5 cm)
Rear Tires	Carlisle <sup>†</sup> ACT HD 26 x 10 x 12-in. (66 x 25.4 x 30.5 cm)
Wheels	12-in. cast-aluminum

DIMENSIONS / CAPACITIES			
LxWxH	312 x 124 x 126 cm		
Wheelbase	208.1 cm		
Ground Clearance	27.9 cm		
Seat Height	87.7 cm		
Dry Weight*	517 kg		
Rack Capacity	Front: 45 kg Rear: 318 kg		
Storage Capacity	Dual-level cargo box with sidewalls and tailgate Rear: 70 L		
Towing Capacity	750 kg		
Fuel Capacity	20.5 L		

<b>FEATURES</b>			
Gauge	Multifunction Digital: Speedometer, tachometer (bar graph RPM, bottom bar numerical RPM), odometer, trip & hour meters, diagnostic center, gear position, engine hour meter, 4 x 4 indicator, temperature and engine lights, fuel gauge, clock	Instrumentation	Lighter type DC outlet in console, standard connector in the back (15-A)
		Lighting	230 W from twin 60-W projectors and dual 55-W reflectors with tail light / brake light
		Seat	Seat with backrest
Winch	1,361 kg WARN† winch with roller fairlead	Anti-theft System	Digitally Encoded Security System (D.E.S.S.™)
T3 features	Seat with backrest, lockable fuel cap, transmission lockable in park mode (P), towing hitch and trailer plug, two front position lamps + directional indicators, extra tail light / brake light + directional		

WARRANTY		
Factory	2 years	



indicators, mirrors, horn



