

ROTAX° ENGINE	800R E-TEC
Engine details	Liquid-cooled, 3-D R.A.V.E.™
Cylinders	2
Displacement	799.5 cc
Bore	82 mm
Stroke	75.7 mm
Maximum engine speed	7900 RPM
Carburation	Electronic Direct Injection
Recommended fuel type	Unleaded
Minimum octane	95
Fuel tank	40 liters
Oil tank capacity (2-stroke)	2,9 liters

<u>COLOUR</u>

DIMENSIONS

Vehicle overall length	3280 mm
Vehicle overall width	1180 mm
Vehicle overall height	1445 mm
Ski stance	996 (+/- 21) mm
Track nominal width	600 mm
Track nominal length	3968 mm
Track profile height	44 mm

POWERTRAIN

Drive clutch type	TRA 7
Driven clutch type	QRS SS
Small sprocket number of teeth	1st gear = 3.23:1 ratio
Large sprocket number of teeth	2nd gear = 1.98:1 ratio
Drive sprocket	8
Brake system	Hydraulic brake with braided steel brake line, plastic master cylinder

SUSPENSION

Front suspension	A-LFS+ with bended lower A-Arms
Front shock	HPG 36
Rear suspension	PPS-6900-A
Center shock	HPG 36
Rear shock	HPG 36

FEATURES

Frame	L-XU
Skis	Blade XC
Seating	Modular, 1+1
Handlebar	U-type steel with hooks, mountain strap
Riser block height	Adjustable 130-205 mm
Starter	Manual, Electric
Reverse	Mechanical (2F-N-R)

Heated throttle lever	Standard
Heated grips	Standard
Gauge	Multifunction
Mirrors	Standard
Windshield	High (510 mm), one piece
Hitch	Standard
Visor Plug front / rear	Front
12V power outlet	Front



